

Schlauch-Kupplungen System Kamlok DIN 2828 / MIL Spec. C-27487

Quick -Couplings / Cam locking



Artikelbezeichnung

Kamlok-

Typ A Adapter mit Innengewinde / Adaptor with Female Thread B.S.P.

Größe		Bronze Messing	Aluminium	Edelstahl / Stainless Steel	Polypropylen- Kunststoff
Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	A050-BR	A050-AL	A050-SS	A050-PP
3/4 "	19	A075-BR	A075-AL	A075-SS	A075-PP
1 "	25	A100-BR	A100-AL	A100-SS	A100-PP
1 1/4 "	32	A125-BR	A125-AL	A125-SS	
1 1/2 "	40	A150-BR	A150-AL	A150-SS	A150-PP
2 "	50	A200-BR	A200-AL	A200-SS	A200-PP
2 1/2 "	65	A250-BR	A250-AL	A250-SS	
3 "	75	A300-BR	A300-AL	A300-SS	A300-PP
4 "	100	A400-BR	A400-AL	A400-SS	A400-PP
5 "	125	A500-BR	A500-AL	A500-SS	A500-PP
6 "	150	A600-BR	A600-AL	A600-SS	A600-PP



Typ F Adapter mit Außengewinde / Adaptor with Male Thread B.S.P.T.

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	F050-BR	F050-AL	F050-SS	F050-PP
3/4 "	19	F075-BR	F075-AL	F075-SS	F075-PP
1 "	25	F100-BR	F100-AL	F100-SS	F100-PP
1 1/4 "	32	F125-BR	F125-AL	F125-SS	
1 1/2 "	40	F150-BR	F150-AL	F150-SS	F150-PP
2 "	50	F200-BR	F200-AL	F200-SS	F200-PP
2 1/2 "	65	F250-BR	F250-AL	F250-SS	
3 "	75	F300-BR	F300-AL	F300-SS	F300-PP
4 "	100	F400-BR	F400-AL	F400-SS	F400-PP
5 "	125	F500-BR	F500-AL	F500-SS	F500-PP
6 "	150	F600-BR	F600-AL	F600-SS	F600-PP



Typ E Adapter mit Schlauchtülle / Adaptor with Hose Tail

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	E050-BR	E050-AL	E050-SS	E050-PP
3/4 "	19	E075-BR	E075-AL	E075-SS	E075-PP
1 "	25	E100-BR	E100-AL	E100-SS	E100-PP
1 1/4 "	32	E125-BR	E125-AL	E125-SS	
1 1/2 "	40	E150-BR	E150-AL	E150-SS	E150-PP
2 "	50	E200-BR	E200-AL	E200-SS	E200-PP
2 1/2 "	65	E250-BR	E250-AL	E250-SS	
3 "	75	E300-BR	E300-AL	E300-SS	E300-PP
4 "	100	E400-BR	E400-AL	E400-SS	E400-PP
5 "	125	E500-BR	E500-AL	E500-SS	E500-PP
6 "	150	E600-BR	E600-AL	E600-SS	E600-PP



Typ DP Endstopfen / Dust Plug

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	DP050-BR	DP050-AL	DP050-SS	DP050-PP
3/4 "	19	DP075-BR	DP075-AL	DP075-SS	DP075-PP
1 "	25	DP100-BR	DP100-AL	DP100-SS	DP100-PP
1 1/4 "	32	DP125-BR	DP125-AL	DP125-SS	
1 1/2 "	40	DP150-BR	DP150-AL	DP150-SS	DP150-PP
2 "	50	DP200-BR	DP200-AL	DP200-SS	DP200-PP
2 1/2 "	65	DP250-BR	DP250-AL	DP250-SS	
3 "	75	DP300-BR	DP300-AL	DP300-SS	DP300-PP
4 "	100	DP400-BR	DP400-AL	DP400-SS	DP400-PP
5 "	125	DP500-BR	DP500-AL	DP500-SS	DP500-PP
6 "	150	DP600-BR	DP600-AL	DP600-SS	DP600-PP

Standard : Gewinde. G = DIN ISO 228 / B.S.P. (IG)
Gewinde. R = DIN 2999 / B.S.P.T. (AG)

NPT- Gewinde : auf Anfrage
NPT- thread : on request

Schlauch-Kupplungen System Kamlok DIN 2828 / MIL Spec. C-27487

Quick -Couplings / Cam locking



Typ D Kupplung mit Innengewinde / Coupler with Female Thread B.S.P.

Größe		Bronze Messing	Aluminium	Edelstahl / Stainless Steel	Polypropylen- Kunststoff
Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	D050-BR	D050-AL	D050-SS	D050-PP
3/4"	19	D075-BR	D075-AL	D075-SS	D075-PP
1"	25	D100-BR	D100-AL	D100-SS	D100-PP
1 1/4"	32	D125-BR	D125-AL	D125-SS	
1 1/2"	40	D150-BR	D150-AL	D150-SS	D150-PP
2"	50	D200-BR	D200-AL	D200-SS	D200-PP
2 1/2"	65	D250-BR	D250-AL	D250-SS	
3"	75	D300-BR	D300-AL	D300-SS	D300-PP
4"	100	D400-BR	D400-AL	D400-SS	D400-PP
5"	125	D500-BR	D500-AL	D500-SS	D500-PP
6"	150	D600-BR	D600-AL	D600-SS	D600-PP



Typ B Kupplung mit Außengewinde / Coupler with Male Thread B.S.P.T.

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	B050-BR	B050-AL	B050-SS	B050-PP
3/4"	19	B075-BR	B075-AL	B075-SS	B075-PP
1"	25	B100-BR	B100-AL	B100-SS	B100-PP
1 1/4"	32	B125-BR	B125-AL	B125-SS	
1 1/2"	40	B150-BR	B150-AL	B150-SS	B150-PP
2"	50	B200-BR	B200-AL	B200-SS	B200-PP
2 1/2"	65	B250-BR	B250-AL	B250-SS	
3"	75	B300-BR	B300-AL	B300-SS	B300-PP
4"	100	B400-BR	B400-AL	B400-SS	B400-PP
5"	125	B500-BR	B500-AL	B500-SS	B500-PP
6"	150	B600-BR	B600-AL	B600-SS	B600-PP



Typ C Kupplung mit Schlauchtülle / Coupler with Hose Tail

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	C050-BR	C050-AL	C050-SS	C050-PP
3/4"	19	C075-BR	C075-AL	C075-SS	C075-PP
1"	25	C100-BR	C100-AL	C100-SS	C100-PP
1 1/4"	32	C125-BR	C125-AL	C125-SS	
1 1/2"	40	C150-BR	C150-AL	C150-SS	C150-PP
2"	50	C200-BR	C200-AL	C200-SS	C200-PP
2 1/2"	65	C250-BR	C250-AL	C250-SS	
3"	75	C300-BR	C300-AL	C300-SS	C300-PP
4"	100	C400-BR	C400-AL	C400-SS	C400-PP
5"	125	C500-BR	C500-AL	C500-SS	C500-PP
6"	150	C600-BR	C600-AL	C600-SS	C600-PP



Typ DC Endkappe / Dust Cap

Zoll/inch	DN	- BR	- AL	- SS	- PP
1/2 "	13	DC050-BR	DC050-AL	DC050-SS	DC050-PP
3/4"	19	DC075-BR	DC075-AL	DC075-SS	DC075-PP
1"	25	DC100-BR	DC100-AL	DC100-SS	DC100-PP
1 1/4"	32	DC125-BR	DC125-AL	DC125-SS	
1 1/2"	40	DC150-BR	DC150-AL	DC150-SS	DC150-PP
2"	50	DC200-BR	DC200-AL	DC200-SS	DC200-PP
2 1/2"	65	DC250-BR	DC250-AL	DC250-SS	
3"	75	DC300-BR	DC300-AL	DC300-SS	DC300-PP
4"	100	DC400-BR	DC400-AL	DC400-SS	DC400-PP
5"	125	DC500-BR	DC500-AL	DC500-SS	DC500-PP
6"	150	DC600-BR	DC600-AL	DC600-SS	DC600-PP

Standard : Gewinde. G = DIN ISO 228 / B.S.P. (IG)

Gewinde. R = DIN 2999 / B.S.P.T. (AG)

NPT- Gewinde : auf Anfrage

NPT- thread : on request

17.07.2013