

## 1/4" - 1" POLY MICRO VALVES

### FEATURES

- 90° rotating handle
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Standard FKM seats and O-Rings except 1". 1" has PTFE seats and O-Rings.

**John Guest®**  
Fitting

The brand "John Guest" is a registered trademark of John Guest International Limited.



### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
LV025V	1/4" FEMALE NPT MICRO VALVE	300	1/4"	3/8"	1
LV038V	3/8" FEMALE NPT MICRO VALVE	300	3/8"	3/8"	1
LV050V	1/2" FEMALE NPT MICRO VALVE	300	1/2"	15/32"	1
LV050SLV	1/2" SIDE LOAD MICRO VALVE	300	1/2"	1/2"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU	QTY
LVHB025V	1/4" HOSE BARB MICRO VALVE	300	1/4"	3/8"	1
LVHB038V	3/8" HOSE BARB MICRO VALVE	300	3/8"	3/8"	1
LVHB050V	1/2" HOSE BARB MICRO VALVE	300	1/2"	3/8"	1
LVHB075V	3/4" HOSE BARB MICRO VALVE	300	3/4"	15/32"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
LV025MTV	1/4" FEMALE X MALE NPT MICRO VALVE	300	1/4"	3/8"	1
LV038MTV	3/8" FEMALE X MALE NPT MICRO VALVE	300	3/8"	3/8"	1
LV038050MTV	3/8" FEMALE X 1/2" MALE NPT MICRO VALVE	300	3/8" x 1/2"	3/8"	1
LV050MTV	1/2" FEMALE X MALE NPT MICRO VALVE	300	1/2"	15/32"	1
LV050100MTV	1/2" FEMALE X 1" MALE NPT MICRO VALVE	300	1/2"	15/32"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
LVHB038050MTV	3/8" HOSE BARB X 1/2" MALE NPT MICRO VALVE	300	1/2"	3/8"	1
LVHB075MTV	3/4" HOSE BARB X 3/4" MALE NPT MICRO VALVE	300	3/4"	1/2"	1
LVHB075100MTV	3/4" HOSE BARB X 1" MALE NPT MICRO VALVE	300	1"	15/32"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
LVPL038MPTV	3/8" FEMALE PUSH LOCK X 3/8" NPT MICRO VALVE FKM	150	3/8"	3/8"	1
LVPL038025MPTV	3/8" FEMALE PUSH LOCK X 1/4" NPT MICRO VALVE FKM	150	1/4"	3/8"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
LVPL025V	1/4" FEMALE PUSH LOCK MICRO VALVE	150	1/4"	3/8"	1
LVPL038V	3/8" FEMALE PUSH LOCK MICRO VALVE	150	3/8"	3/8"	1
LVPL050V	1/2" FEMALE PUSH LOCK MICRO VALVE	150	1/2"	15/32"	1

### MICRO VALVES

PART NO	DESCRIPTION	MAX PSI	THREAD SIZE	OPENING THRU BALL	QTY
MLV100V	1" MANIFOLD MICRO VALVE	300	1"	1/2"	1

### ½" - 2" 4 BOLTED VALVES



V100FP

V125

V200

#### 4 BOLTED VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU	QTY	REPLACEMENT HANDLE	REPAIR KIT
V050	½" FULL PORT VALVE	300	½"	¾"	24/box	V10153A	V07200
V075	¾" FULL PORT VALVE	300	¾"	¾"	24/box	V10153A	V07200
V100	1" STANDARD PORT VALVE	225	1"	¾"	24/box	V10153A	V07200
V100FP	1" FULL PORT VALVE	300	1"	1"	24/box	V10153A	V10200
V125	1¼" STANDARD PORT VALVE	300	1¼"	1"	24/box	V10153A	V10200
V125FP	1¼" FULL PORT VALVE	225	1¼"	1½"	24/box	V20153	V20200
V150	1½" FULL PORT VALVE	225	1½"	1½"	24/box	V20153	V20200
V200	2" STANDARD PORT VALVE	225	2"	1½"	24/box	V20153	V20200

#### FEATURES

- FKM seals.
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Self-aligning ball moves freely against the PTFE seats for smooth operation. The valve opens and closes with very little pressure on the handle.
- Ball is diamond turned, after molding, to make it spherically perfect, which provides precise contact between ball and seats.
- PTFE self-lubricating stem bushings and seats cannot stick or bind.
- Stainless steel bolts.

#### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

### VALVE ACCESSORIES



V25270

V25271

#### FEATURES

- 304 stainless steel construction
- Installs under valve handle
- Comes complete with handle and locking device
- Padlock not included

#### VALVE ACCESSORIES

PART NO	DESCRIPTION	FITS VALVES	QTY
VL20153	LOCKING DEVICE	V125, V150, V200	1
V10270	STRAIGHT MOUNTING BRACKET	V100FP, V125	1
V10271	90° MOUNTING BRACKET	V100FP, V125	1
V25270	STRAIGHT MOUNTING BRACKET	V125FP, V150, V200	1
V25271	90° MOUNTING BRACKET	V125FP, V150, V200	1
V10153138	1" X 1⅜" HANDLE OFFSET	V100FP, V125	1
V20153138	2" FP X 1⅜" HANDLE OFFSET	V125FP, V150, V200	1
V25153138	2" FP X 1⅜" HANDLE OFFSET	V200FP	1



## 2"-4" 6 BOLTED VALVES

### FEATURES

- FKM seals.
- Precision molded polypropylene is reinforced with fiberglass for additional strength.
- Self-aligning ball moves freely against the PTFE seats for smooth operation. The valve opens and closes with very little pressure on the handle.
- Ball is diamond turned, after molding, to make it spherically perfect, which provides precise contact between ball and seats.
- PTFE self-lubricating stem bushings and seats cannot stick or bind.
- Stainless steel bolts.

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



### 6 BOLTED VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
V200FP	2" FULL PORT VALVE	225	2"	2"	8/box	V25153	V25200
V300	3" STANDARD PORT VALVE	225	3"	2½"	8/box	V25153	V30200
V300FP	3" FULL PORT VALVE	200	3"	3"	6/box	V25153	V35200
V400	4" STANDARD PORT VALVE	100	4"	3½"	4/box	V25153	V40200
VFMT200FP	2" FULL PORT VALVE W/ F ADAPTER	225	2"	2"	6/box	V25153	V25200

## VALVE ACCESSORIES

### FEATURES

- Stainless steel hardware
- Locks in open and closed positions
- Locking handle replaces standard handle (sold separately)
- Padlock not included



### VALVE ACCESSORIES

PART NO	DESCRIPTION	FITS VALVES	QTY
VL25153	LOCKING HANDLE	V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH	1
V25270	STRAIGHT MOUNTING BRACKET	V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH	1
V25271	90° MOUNTING BRACKET	V200FP, V300, V300FP, V400, VFMT200FP, VFMT200FPSH	1

### 2" FULL PORT BOLTED BALL VALVES



VFMT204FP

V204FP

#### 4 BOLTED FULL PORT VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
VFMT204FP	2" FULL PORT VALVE MALE NPT X MALE ADAPTER	150	2"	2"	6/box	V25153	V25200
V204FP	2" FULL PORT VALVE	150	2"	2"	8/box	V25153	V25200

#### FEATURES

- FKM seals
- Stainless steel bolts
- PTFE self-lubricating stem bushings and seats cannot stick or bind
- Precision molded in fiberglass reinforced polypropylene
- Self-aligning ball moves freely against the PTFE seats for smoother operation
- Valve opens and closes with very little pressure on the handle
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats

#### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

### 2" FULL PORT ANSI FLANGE BOLTED BALL VALVES



VSF200FFAF

VSMT200FFAF

#### 4 BOLTED FULL PORT VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
VSF200FFAF	2" FULL PORT VALVE MALE ADAPTER X 2" ANSI FLANGE	200	2"	2"	6/box	V25153SH	VS25200
VSMT200FFAF	2" FULL PORT VALVE	200	2"	2"	6/box	V25153SH	VS25200

#### FEATURES

- 100% PTFE seats
- FKM seals
- Glass-filled polypropylene
- Unique compact design
- Lightweight
- Gaskets featured on page 73

#### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

## 2" STANDARD PORT STUBBY BALL VALVES

### FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- Multiple design options
- Unique patented compact design
- Lightweight
- All PTFE seals

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VSF200



VSMT200



VSFMT200



VSFHB200

### 2" STANDARD PORT STUBBY VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
VSF200	2" MALE ADAPTER X 2" FEMALE NPT	100	2"	1½"	24/box	VS20152SH	VS20200
VSMT200	2" MALE NPT X 2" FEMALE NPT	100	2"	1½"	24/box	VS20152SH	VS20200
VSFMT200	2" MALE ADAPTER X 2" MALE NPT	225	2"	1½"	24/box	VS20152SH	VS20200
VSFHB200	2" MALE ADAPTER X 2" HOSE BARB	100	2"	1½"	24/box	VS20152SH	VS20200



**2" FULL PORT STUBBY BALL VALVES**



VSMT204FP



VSF204FP



VS204FP



VSFMT204FP



VSFMT204HSFP

**FEATURES**

- Stainless steel bolts
- 100% PTFE ball seats
- Glass reinforced polypropylene
- Unique patented compact design
- Lightweight
- FKM body seals

**REPAIR KIT INCLUDES:**

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring

**2" STANDARD PORT STUBBY VALVES**

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
VSMT204FP	2" MALE NPT X 2" FEMALE NPT	200	2"	2"	18/BOX	VS25153	VS25200
VSF204FP	2" MALE ADAPTER X 2" FEMALE NPT	100	2"	2"	18/BOX	VS25153	VS25200
VS204FP	2" FEMALE NPT X 2" FEMALE NPT	225	2"	2"	18/BOX	VS25153	VS25200
VSFMT204FP	2" MALE ADAPTER X 2" MALE NPT	150	2"	2"	18/BOX	VS25153	VS25200
VSFMT204HSFP	2" FP MALE ADAPTER X 2" MALE NPT W/ SS BALL, STEM & HANDLE	150	2"	2"	18/BOX	VS25153SS	VSSH25200

## 3" STANDARD PORT STUBBY BALL VALVES

### FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- FKM body seals
- Unique patented compact design
- Lightweight
- All PTFE seals

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



### 3" STANDARD PORT STUBBY VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE STRAIGHT	REPLACEMENT HANDLE SHORT	REPAIR KIT
VSF300	3" FEMALE NPT X 3" MALE ADAPTER	100	3"	2½"	6/box	V25153	V25153SH	VS30200
VSMT300	3" FEMALE NPT X 3" MALE NPT	100	3"	2½"	6/box	V25153	V25153SH	VS30200
VSFMT300	3" MALE NPT X 3" MALE ADAPTER	225	3"	2½"	6/box	V25153	V25153SH	VS30200

## 3" FULL PORT STUBBY BALL VALVES

### FEATURES

- Stainless steel bolts
- Glass reinforced polypropylene
- FKM body seals
- Unique patented compact design
- Lightweight
- All PTFE ball seats

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



### 3" FULL PORT STUBBY VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPLACEMENT HANDLE	REPAIR KIT
VSFMT300FP	3" FULL PORT MALE ADAPTER X 3" MALE NPT	100	3"	3"	6/box	V25153	VS35200
VSFMT300HSFP	3" FULL PORT MALE ADAPTER X 3" MALE NPT W/SS BALL, STEM & HANDLE	100	3"	3"	6/box	VS30153SS	VSSH35200

### 3 WAY BOTTOM LOAD BALL VALVES

#### FEATURES

- Stainless steel bolts
- Precision molded in fiberglass reinforced polypropylene for additional strength
- Self-aligning ball moves freely against the PTFE seats for smooth operation
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats
- PTFE self-lubricating stem bushings and seats
- FKM body seals
- Directional flow, right or left. Valve can be turned off to stop flow



### 3 WAY BOTTOM LOAD VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	HANDLE TYPE	REPLACEMENT HANDLE	REPAIR KIT
V075BL	¾" 3-WAY BOTTOM LOAD VALVE	200	¾"	1"	18/box	T	V10353TB	V10300SL
V100BL	1" 3-WAY BOTTOM LOAD VALVE	225	1"	1"	18/box	T	V10353TB	V10300SL
V125BL	1¼" 3-WAY BOTTOM LOAD VALVE	300	1¼"	1½"	12/box	T	V20353TB	V15300SL
V150BL	1½" 3-WAY BOTTOM LOAD VALVE	225	1½"	1½"	12/box	T	V20353TB	V15300SL
V200BL	2" 3-WAY BOTTOM LOAD VALVE	200	2"	2"	8/box	STRAIGHT	V25353B	V25200BL

### 3 WAY SIDE LOAD BALL VALVES

#### FEATURES

- Stainless steel bolts
- Precision molded in fiberglass reinforced polypropylene for additional strength
- Self-aligning ball moves freely against the PTFE seats for smooth operation
- Ball is diamond turned after molding to make it spherically perfect, which provides precise contact between ball and seats
- PTFE self-lubricating stem bushings and seats
- FKM body seals
- Directional flow, right or left. Valve cannot be turned off to stop flow



### 3 WAY SIDE LOAD VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	HANDLE TYPE	REPLACEMENT HANDLE	REPAIR KIT
V075SL	¾" 3-WAY SIDE LOAD VALVE	200	¾"	1"	18/box	STRAIGHT	V10153A	V10300SL
V100SL	1" 3-WAY SIDE LOAD VALVE	200	1"	1"	18/box	STRAIGHT	V10153A	V10300SL
V125SL	1¼" 3-WAY SIDE LOAD VALVE	300	1¼"	1½"	12/box	T	V20353TS	V15300SL
V150SL	1½" 3-WAY SIDE LOAD VALVE	225	1½"	1½"	12/box	T	V20353TS	V15300SL
V200SL	2" 3-WAY SIDE LOAD VALVE	225	2"	2"	8/box	STRAIGHT	V25153SH	V25200BL



# VALVES

## 1½" - 2" NOZZLE VALVES

### FEATURES

- Lightweight hose end valve for convenient transfer of liquids into drums, tanks etc
- Angled end flange with 8" long polypropylene fill spout
- All stainless steel bolts

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VA150

VA200FP

### 1½"-2" NOZZLE VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	FEMALE NPT	QTY	REPLACEMENT HANDLE	REPAIR KIT
VA150	1½" NOZZLE VALVE WITH 90° ELBOW	225	1½" x 8"	1½"	1½"	12/box	V20152	V20200
VA200	2" NOZZLE VALVE WITH 90° ELBOW	200	2" x 8"	1½"	2"	12/box	V20152	V20200
VA200FP	2" FP NOZZLE VALVE WITH 90° ELBOW	225	2" x 8"	2"	2"	6/box	V25152	V25200

## 1" DISPENSING NOZZLES

### FEATURES

- Glass reinforced polypropylene
- 304 stainless steel handle, spring and pin
- FKM rubber parts only
- Resists corrosion

### REPAIR KIT INCLUDES:

- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



VN100

V10161

### 1" DISPENSING NOZZLE

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	FEMALE NPT	QTY	REPLACEMENT HANDLE	REPAIR KIT
VN100	1" DISPENSING NOZZLE	150	1"	N/A	1"	1	VN10253	VN10200
V10161	1" NOZZLE PIPE FOR USE WITH V100, V100FP, UV100FP, SUV100FP	N/A	1"	N/A	1"	1		



SUV125FP



MSUV100FP

### 1/2"-2" SINGLE UNION SPINWELD VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
SUV050FP	1/2" FULL PORT SINGLE UNION SPINWELD VALVE	300	1/2"	1/2"	1
SUV075FP	3/4" FULL PORT SINGLE UNION SPINWELD VALVE	300	3/4"	3/4"	1
SUV100FP	1" FULL PORT SINGLE UNION SPINWELD VALVE	300	1"	1"	1
SUV125FP	1 1/4" FULL PORT SINGLE UNION SPINWELD VALVE	300	1 1/4"	1 1/4"	1
SUV150FP	1 1/2" FULL PORT SINGLE UNION SPINWELD VALVE	300	1 1/2"	1 1/2"	1
SUV200FP	2" FULL PORT SINGLE UNION SPINWELD VALVE	200	2"	2"	1
MSUV100FP	1" MANIFOLD FULL PORT SINGLE UNION SPINWELD VALVE	300		1"	1

### 1/2" - 2" SINGLE UNION SPINWELD VALVES

#### FEATURES

- Precision molded in glass reinforced polypropylene for strength and chemical resistance
- PTFE seats for smooth and proper sealing characteristics
- EPDM O-rings to handle most fertilizers and many chemicals
- Double O-rings in stem area for extra sealing protection
- Interlocking body and end plate to allow easy thread connection when installing valves



### 1/2"-2" SINGLE UNION VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
UV050FP	1/2" FULL PORT SINGLE UNION VALVE	300	1/2"	3/4"	1
UV075FP	3/4" FULL PORT SINGLE UNION VALVE	300	3/4"	3/4"	1
UV100FP	1" FULL PORT SINGLE UNION VALVE	300	1"	1"	1
UV125FP	1 1/4" FULL PORT SINGLE UNION VALVE	225	1 1/4"	1 1/4"	1
UV150FP	1 1/2" FULL PORT SINGLE UNION VALVE	200	1 1/2"	1 1/2"	1
UV200FP	2" FULL PORT SINGLE UNION VALVE	300	2"	2"	1

### 1/2" - 2" SINGLE UNION VALVES

#### FEATURES

- Precision molded in glass reinforced polypropylene for strength and chemical resistance
- PTFE seats for smooth and proper sealing characteristics
- Double O-rings in stem area for extra sealing protection
- Interlocking body and end plate to allow easy thread connection when installing valves

# VALVES

## 1/2" - 3" CHECK VALVES

### FEATURES

- One piece construction
- Glass reinforced polypropylene
- 316 stainless steel springs
- EPDM gasket



### 1/2"-3" CHECK VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	QTY
CV050	1/2" CHECK VALVE	300	1/2"	1
CV100MT	1" MALE X FEMALE NPT CHECK VALVE	300	1"	1
CV100	1" CHECK VALVE	300	1"	1
CV221	2" FULL PORT CHECK VALVE	300	2"	1
CV300	3" FULL PORT CHECK VALVE W/ 5 LB SPRING	300	3"	1
CV301	3" FULL PORT CHECK VALVE W/1/2 LB SPRING	300	3"	1

## 1/4" - 3" STAINLESS STEEL FULL PORT VALVES

### FEATURES

- 316 stainless steel
- Blow out proof stem
- All valves 100% tested by air, under water at 100 PSI in open and closed positions
- Latch locking handle performs in both open and closed positions
- Mounting pad
- PTFE seals and seats



### 1/4"-3" STAINLESS STEEL FULL PORT VALVES

PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	REPAIR KIT
VSS025	1/4" SS FULL PORT VALVE	1000	1/4"	1/4"	1	VSS02500
VSS038	3/8" SS FULL PORT VALVE	1000	3/8"	3/8"	1	VSS02500
VSS050	1/2" SS FULL PORT VALVE	1000	1/2"	1/2"	1	VSS05200
VSS075	3/4" SS FULL PORT VALVE	1000	3/4"	3/4"	1	VSS07200
VSS100	1" SS FULL PORT VALVE	1000	1"	1"	1	VSS10200
VSS150	1 1/2" SS FULL PORT VALVE	1000	1 1/2"	1 1/2"	1	VSS15200
VSS200	2" SS FULL PORT VALVE	1000	2"	2"	1	VSS25200
VSS300	3" SS FULL PORT VALVE	1000	3"	3"	1	VSS35200

## 3/4" - 1" PINCH VALVES

### FEATURES

- Open position allows full unobstructed flow of 50-60 GPM
- Air pressure collapses the internal rubber sleeve to provide positive shut off
- Standard EPDM rubber bladder seal and FKM available
- Female NPT threads
- ATTENTION: Normally an open valve and has a maximum liquid pressure of 70 PSI. Pressure differential = pressure it takes to close valve



### 3/4"-1" PINCH VALVES

PART NO	DESCRIPTION	GASKET	MAX PSI	PIPE SIZE	PRESSURE DIFFERENTIAL	QTY
PV075	3/4" X 3/4" PINCH VALVE	EPDM	300	3/4"	15 TO 20 PSI	1
PV100	1" X 1" PINCH VALVE	EPDM	300	1"	15 TO 20 PSI	1
PV100V	1" X 1" PINCH VALVE	FKM	300	1"	15 TO 20 PSI	1
PV100-075	1" X 3/4" PINCH VALVE	EPDM	300	1" X 3/4"	15 TO 20 PSI	1
PV100-075V	1" X 3/4" PINCH VALVE	FKM	300	1" X 3/4"	15 TO 20 PSI	1
PV100-075B	1" X 3/4" FEMALE COUPLER PINCH VALVE	EPDM	300	1" X 3/4"	15 TO 20 PSI	1
PV10265	BLADDER	EPDM	N/A			1
PV10265V	BLADDER	FKM	N/A			1